

Printing date 12.12.2013

. 1.1 Product identifier

. Manufacturer/Supplier: Bison International Dr.A.F.Philipsstraat 9


2 Hazards identification

GHS02

GHS08

NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800

*



H351 Suspected of causing cancer. Carc. 2

GHS07

Eye Irrit. 2 H319 Causes serious eye irritation. H335 May cause respiratory irritation. STOT SE 3

Classification according to Directive 67/548/EEC or Directive 1999/45/EC х Xn; Harmful R40: Limited evidence of a carcinogenic effect. Xi; Irritant Irritating to eyes and respiratory system. R36/37: F; Highly flammable R11: Highly flammable.

> (Contd. on page 2) GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2013 Version number 14 Revision: 12.12.2013

Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE

(Contd. of page 1) . Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. . Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. . 2.2 Label elements . Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. . Code letter and hazard designation of product: Xn Harmful F Highly flammable . Hazard-determining components of labelling: tetrahydrofuran . Risk phrases: 11 Highly flammable. 36/37 Irritating to eyes and respiratory system. Limited evidence of a carcinogenic effect. 40 Safety phrases: 9 Keep container in a well-ventilated place. 16 Keep away from sources of ignition - No smoking. 25 Avoid contact with eyes. 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. 46 If swallowed, seek medical advice immediately and show this container or label. 61 Avoid release to the environment. Refer to special instructions/safety data sheets. . 2.3 Other hazards . Results of PBT and vPvB assessment . **PBT:** Not applicable. . **vPvB:** Not applicable. 3 Composition/information on ingredients . 3.2 Mixtures . Description: Adhesive . Dangerous components: CAS: 109-99-9 50-100% tetrahydrofuran 🗙 Xn R40; 🗙 Xi R36/37; 🗼 F R11 EINECS: 203-726-8 Reg.nr.: 01-2119444314-46 R19 Carc. Cat. 3 🚸 Flam. Liq. 2, H225; 🚸 Carc. 2, H351; • Eye Irrit. 2, H319; STOT SE 3, H335 (Contd. on page 3)

*

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2013 Version number 14 Revision: 12.12.2013 Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE (Contd. of page 2) CAS: 108-94-1 cyclohexanone 10-25% EINECS: 203-631-1 🗙 Xn R20 Reg.nr.: 01-2119453616-35 R10 🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H332 CAS: 78-93-3 methyl ethyl ketone 2.5-10% EINECS: 201-159-0 🗙 Xi R36; 🔥 F R11 Reg.nr.: 01-2119457290-43 R66-67 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336 . Additional information: For the wording of the listed risk phrases refer to section 16. 4 First aid measures . 4.1 Description of first aid measures . After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stable in side position for transportation. . After skin contact: Generally the product does not irritate the skin. . After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. . After swallowing: Do not induce vomiting; call for medical help immediately. . 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. . 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available. 5 Firefighting measures . 5.1 Extinguishing media . Suitable extinguishing agents: Water haze Alcohol resistant foam Fire-extinguishing powder Carbon dioxide . For safety reasons unsuitable extinguishing agents: Water with full jet . 5.2 Special hazards arising from the substance or mixture No further relevant information available. . 5.3 Advice for firefighters . Protective equipment: Mount respiratory protective device. . Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system. 6 Accidental release measures . 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2013 Version number 14 Revision: 12.12.2013

Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE

		(Contd. of page 3)
•	. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, binders, sawdust).	universal
	Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.	
•	6.4 Reference to other sections	
	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.	
	See Section 13 for disposal information.	
7	7 Handling and storage	
•	 7.1 Precautions for safe handling Ensure good interior ventilation, especially at floor level. (Fumes than air). 	are heavier
•	Information about fire - and explosion protection:	
	Keep ignition sources away - Do not smoke. Protect against electrostatic charges.	
	. 7.2 Conditions for safe storage, including any incompatibilities	
	. Storage:	
	. Requirements to be met by storerooms and receptacles: Store in a co	
	. Information about storage in one common storage facility: Not requi . Further information about storage conditions:	red.
•	Keep receptacle tightly sealed.	
	Store in cool, dry conditions in well sealed receptacles.	
•	. 7.3 Specific end use(s) No further relevant information available.	
~	8 Exposure controls/personal protection	
8	- Inposate concluss/personal protection	
_	 Additional information about design of technical facilities: No further data; see item 7. 	
•	Additional information about design of technical facilities:	
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone 	ace:
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV 	
•	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm 	
	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV Additional information: The lists valid during the making were used 8.2 Exposure controls 	
· · ·	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV Additional information: The lists valid during the making were used 8.2 Exposure controls Personal protective equipment: 	
· · ·	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV Additional information: The lists valid during the making were used 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: 	as basis.
· · ·	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV Additional information: The lists valid during the making were used 8.2 Exposure controls Personal protective and hygienic measures: The usual precautionary measures are to be adhered to when handling Keep away from foodstuffs, beverages and feed. 	as basis.
· · ·	 Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workpl 109-99-9 tetrahydrofuran WEL () Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Sk 108-94-1 cyclohexanone WEL () Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm Sk, BMGV 78-93-3 methyl ethyl ketone WEL () Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV Additional information: The lists valid during the making were used 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling 	as basis.

*

*

GB



Safety data sheet according to 1907/2006/EC, Article 31 Revision: 12.12.2013 Printing date 12.12.2013 Version number 14 Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE (Contd. of page 4) Avoid contact with the eyes and skin. . Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended. . Protection of hands: Solvent resistant gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. . Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. . For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: PVC or PE gloves . Eye protection: Tightly sealed goggles . Body protection: Solvent resistant protective clothing 9 Physical and chemical properties . 9.1 Information on basic physical and chemical properties . General Information . Appearance: Form: Fluid Colour: According to product specification . Odour: Characteristic . Odour threshold: Not determined. . pH-value: Not determined. . Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 65 °C . Flash point: < 0 °C • Flammability (solid, gaseous): Not applicable. . Ignition temperature: 230 °C . Decomposition temperature: Not determined. . Self-igniting: Product is not selfigniting. (Contd. on page 6) GB



Safety data sheet

Version number 14	Revision: 12.12.2013		
500ML*12 ENDE			
	(Contd. of page 5)		
	osive. However, formation of r mixtures are possible.		
1.3 Vol % 12.0 Vol %			
200 hPa			
0.989 g/cm ³ Not determined. Not determined. Not determined.			
with Not miscible or diff	ficult to mix.		
anol/ Not determined.			
2500 mPas Not determined. 20.9 % No further relevant	information available.		
<pre>10 Stability and reactivity . 10.1 Reactivity . 10.2 Chemical stability . Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. . 10.3 Possibility of hazardous reactions No dangerous reactions known. . 10.4 Conditions to avoid No further relevant information available. . 10.5 Incompatible materials: No further relevant information available. . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.</pre>			
11 Toxicological information			
 11.1 Information on toxicological effects Acute toxicity: LD/LC50 values relevant for classification: 109-99-9 tetrahydrofuran Oral LD50 3000 mg/kg (rat) Primary irritant effect: on the skin: No irritant effect. on the eye: Irritating effect. Sensitization: No sensitizing effects known. Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant 			
	500ML*12 ENDE Product is not explo explosive air/vapour 1.3 Vol % 12.0 Vol % 200 hPa 0.989 g/cm ³ Not determined. Not determined. Not determined. Not determined. 2500 mPas Not determined. 2500 mPas Not determined. 20.9 % No further relevant itions to be avoided: ording to specifications. s reactions No dangerous of further relevant informat: No further relevant informat: No further relevant informat: No further relevant informat: gical effects classification: ect. t. g effects known. ormation: ing dangers according to the state of the section of the sec		

*

*



Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 12.12.2013

Version number 14

Revision: 12.12.2013

Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE

(Contd. of page 6)





Safety data sheet according to 1907/2006/EC, Article 31 Printing date 12.12.2013 Version number 14 Revision: 12.12.2013 Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE (Contd. of page 7) . 14.4 Packing group . ADR, IMDG, IATA III . 14.5 Environmental hazards: . Marine pollutant: No Warning: Flammable liquids. . 14.6 Special precautions for user . Danger code (Kemler): 33 . EMS Number: F-E,S-D . 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. . Transport/Additional information: . ADR . Limited quantities (LQ) 5L . Transport category 3 . Tunnel restriction code D/E . IMDG . Remarks: Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2 . UN "Model Regulation": UN1133, ADHESIVES, special provision 640H, 3, III 15 Regulatory information . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture . Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. . Code letter and hazard designation of product: Xn Harmful F Highly flammable . Hazard-determining components of labelling: tetrahydrofuran . Risk phrases: 11 Highly flammable. 36/37 Irritating to eyes and respiratory system. Limited evidence of a carcinogenic effect. 40 . Safety phrases: 9 Keep container in a well-ventilated place. 16 Keep away from sources of ignition - No smoking. 25 Avoid contact with eyes. 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. 46 If swallowed, seek medical advice immediately and show this container or label. 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

(Contd. on page 9)

GB



Safety data sheet according to 1907/2006/EC, Article 31 Version number 14 Revision: 12.12.2013 Printing date 12.12.2013 Trade name: GRIFFON UNI-100 BOT 500ML*12 ENDE (Contd. of page 8) . National regulations: . Technical instructions (air): . Class Share in % NK 50-100 . Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. . 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. . Relevant phrases Highly flammable liquid and vapour. H225 Flammable liquid and vapour. H226 H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336 H351 Suspected of causing cancer. R10 Flammable. R11 Highly flammable. R19 May form explosive peroxides. R20 Harmful by inhalation. Irritating to eyes. R36 R36/37 Irritating to eyes and respiratory system. Limited evidence of a carcinogenic effect. R40 R66 Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. R67 . Department issuing MSDS: QESH Department • Contact: Reach coördinator * Data compared to the previous version altered.

*